VASNER

Required information on electric infrared heating panels

Model: Zipris S with chrome frame (600 watts)

Item	Symbol	Value	Unit	
Heat output				
Nominal heat output	P _{nom}	0,6	kW	
Minimum heat output (indicative)	P _{min}	N/A	kW	
Maximum continuous heat output	P _{max,c}	0,6	kW	
Auxiliary power consumption				
At nominal heat output	el _{max}	0,609	kW	
At minimum heat output	el _{min}	N/A	kW	
In standby mode	el _{SB}	N/A	kW	

The information given refers only to the heating panel.

According to EU Regulation (EU) 2015/1188, electric heaters must be controlled with an electronic room temperature controller (thermostat) which fulfils the criteria of weekday control and window-open-detection or e.g. adaptive control of the start of heating, which are listed here in full.

For compliant operation, please choose one of our electronic thermostats for this heating element, e.g. the VASNER VFTB thermostat set, or use an existing system that meets these criteria.

Only for electric storage heaters: Type of regulation of the heat supply (please select one option) Manual control of the heat supply via integrated thermostat Manual control of the heat supply with feedback of the room and / or outdoor temperature Electronic control of the heat supply with feedback of the room and / or outdoor temperature Fan-assisted heat output / room temperature control (please select one option) Single-stage heat output, no room temperature control Two or more manually adjustable steps, no room temperature control Room temperature control via	Δ
heat supply via integrated thermostat Manual control of the heat supply with feedback of the room and / or outdoor temperature Electronic control of the heat supply with feedback of the room and / or outdoor temperature Fan-assisted heat output Type of heat output / room temperature control (please select one option) Single-stage heat output, no room temperature control Two or more manually adjustable steps, no room temperature control Room temperature control via	Δ
Manual control of the heat supply with feedback of the room and / or outdoor temperature Electronic control of the heat supply with feedback of the room and / or outdoor temperature Fan-assisted heat output Type of heat output / room temperature control (please select one option) Single-stage heat output, no room temperature control Two or more manually adjustable steps, no room temperature control Room temperature control	Δ
Electronic control of the heat supply with feedback of the room and / or outdoor temperature Fan-assisted heat output Type of heat output / room temperature control (please select one option) Single-stage heat output, no room temperature control Two or more manually adjustable steps, no room temperature control Room temperature control	
Type of heat output / room temperature control (please select one option) Single-stage heat output, no room temperature control Two or more manually adjustable steps, no room temperature control Room temperature control via	Α
/ room temperature control (please select one option) Single-stage heat output, no room temperature control Two or more manually adjustable steps, no room temperature control Room temperature control via	
no room temperature control Two or more manually adjustable steps, no room temperature control Room temperature control via	
adjustable NC steps, no room temperature control Room temperature control via	5
Room temperature control via)
mechanical thermostat)
With electronic NC room temperature control)
Electronic room temperature control and time-of-day control)
Electronic room temperature control and weekday regulation)
Other control options (multiple answers possible)	
Room temperature control with occupancy detection)
Room temperature control with open window detection	
With remote control option NC With adaptive control of the)
start of heating NC	١.
With operating time limitation NC With black bulb sensor NC	

Contact details MankeTech GmbH // VASNER - Stahlstr. 27 - 33415 Verl - Germany